

7. Homework

Due **11/15/16** at the beginning of class

1. Union by Weight (3 points)

Consider a disjoint-set forest implementation that uses union by weight only. Give a sequence of m MAKE-SET, UNION, and FIND-SET operations, n of which are MAKE-SET operations, that takes $\Omega(m \log n)$ time.

2. Link Before Find (4 points)

In a disjoint-set forest implementation, the UNION operation is implemented as $\text{UNION}(x, y) = \text{LINK}(\text{FIND-SET}(x), \text{FIND-SET}(y))$.

Consider a disjoint-set forest implementation that uses both union by weight and path compression. Show that any sequence of m MAKE-SET, FIND-SET, and LINK operations, where all the LINK operations appear before any of the FIND-SET operations, takes only $O(m)$ time.

Hint: Use amortized analysis, possibly the accounting method.

3. Dijkstra variants (5 points)

(a) Let G be a directed graph with non-negative edge weights. Consider changing the condition in the while loop of Dijkstra's algorithm to $|Q| > 1$. Prove that at the end of the algorithm the d -values contain the shortest path weights (so, the shortest path weights are correctly computed even when skipping the last iteration from Dijkstra's algorithm).

(b) Let G be a directed graph with non-negative edge weights. Consider changing the condition in the while loop of Dijkstra's algorithm to $|Q| > 2$. Show that at the end of the algorithm the d -values do not necessarily contain the shortest path weights (give a counter-example).

4. Negative edge weights (3 points)

Suppose the weighted, directed graph $G = (V, E)$ has a special structure in which edges that leave the source vertex s may have negative weights. All other edge weights are nonnegative, and there are no negative-weight cycles. Show that Dijkstra's algorithm correctly finds shortest paths from s in G .

5. Negative-weight cycle (4 points)

Given a directed weighted connected graph $G = (V, E)$ with real edge weights (i.e., negative edge weights are allowed). Give an algorithm that detects **and prints** out a negative-weight cycle if G contains a negative-weight cycle. (Do not use Floyd-Warshall's algorithm.) What is the runtime of your algorithm?